

Solvision QL Series Array Wall Mount Speaker SVQL80, SVQL120

Water and dust protected IP55

Weather Luxury Tone Column For A Premium Audio Experience

The Solvision Wall mount QL Series universal surface speakers are compact systems with rugged HIPS housing to ensure its durability and sound quality. This series of speakers rated to IP55. Designed for widely-using.

Features

- 1. Construction and Durability:**
 - Aluminium casing for strong corrosion resistance.
 - Can withstand various weather conditions, including sun, rain, sand, and snow.
- 2. Sound Quality:**
 - Exceptional sound quality, Bass-reflex type enclosure.
 - Extraordinary sound reproduction.
 - Transparent, bright, and soft treble that is not annoying.
 - Excellent mid and high-frequency response.
- 3. Design and Application:**
 - All-weather cabinet design suitable for professional audio and commercial audio markets.
 - Ideal for various outdoor and indoor spaces: squares, factories, playgrounds, parking lots, terminals, and stations.
 - Designed for constant voltage and fixed impedance public address systems.
- 4. Speaker Components:**
 - 1-inch tweeter for clear and crisp high frequencies.
 - 4-inch cone woofer for powerful and well-defined bass.
 - Strong unit power for robust audio performance.
 - Directivity Angle Horizontal >120°, Vertical >20°
- 5. Mounting and Installation:**
 - Equipped with mounting brackets for easy installation.
 - Input connector - Speakon/Banana
- 6. Versatility:**
 - Suitable for a wide range of applications due to its all-weather design and durable construction.
 - Compatible with constant voltage and fixed impedance PA systems.
- 7. Professional Use:**
 - Tailored for professional audio applications, ensuring high-quality sound in various environments.



MODEL NO.	SV-QL80	SV-QL80L	SV-QL120	SV-Q120L
Rated Power	100W	100W	140W	140W
Program Power	160W	160W	240W	240W
Input	100V	8 Ω	100V	8 Ω
Sensitivity	(1W/1M): 97dB±3dB	(1W/1M): 97dB±3dB	(1W/1M): 98dB±3dB	(1W/1M): 98dB±3dB
Frequency Response	150-20KHz	150-20KHz	150-20KHz	150-20KHz
SPL	128dB±3dB	128dB±3dB	138dB±3dB	138dB±3dB
Speaker unit	4*4"bass+1"high	4*4"bass+1"high	6*4"bass+1"high	6*4"bass+1"high
Dimension	132x130x645mm	132x130x645mm	132x130x880mm	132x130x880mm
Weight	8.6kg	8.6kg	13kg	13kg
Safety	CE,FCC, RoHS,(ISO 9001:2015 14001:2015 ,45001:2018, 27001:2022 -IAF Certified)	CE,FCC, RoHS,(ISO 9001:2015 14001:2015 ,45001:2018, 27001:2022 -IAF Certified)	CE,FCC, RoHS,(ISO 9001:2015 14001:2015 ,45001:2018, 27001:2022 -IAF Certified)	CE,FCC, RoHS,(ISO 9001:2015 14001:2015 ,45001:2018, 27001:2022 -IAF Certified)

SOLVISION TECHNOLOGY

27 Elder Road, Working
Surrey GU24 9HB UK
info@solvisionav.com

9 A, Blackwood Avenue,
Mentone, VIC- 3194
salesaustralia@solvisionav.com

629 Redstone Drive NE,
Calgary AB, T3N, 1KB Alberta
salescanada@solvisionav.com

SOLVISION INDIA

357-B, Udyog Vihar Phase 6, SECTOR
37, Pace City II Gurugram Haryana-
122001 -
salesindia@solvisionav.in