

Ultra-thin LCD Monitor Lift with Retractable Screen

Product Description

SVAML-17.3

The motorised multi-point balanced lifting retractable monitor's lightweight design is based on a thin LED monitor lift. The panel surface, the monitor shell, and the housing are all made of aluminium alloy material. Hidden LED monitor in office furniture. The FHD screen of the monitor lift can be retractable rising up and down vertically. The monitor lifts up from the tabletop automatically by the controller, motorising the screen down and hiding it under the table when finished using. The screen inside the LCD monitor lift mechanism would be powered off if lowered to the bottom accordingly. The screen will power on automatically if reached the top. It's a whole system design with an integrated FHD screen with a motorized lift.



Features

- Light Decentralized design, full aluminium alloy material for the top surface panel, monitor shell and bottom housing, brushed aluminium silver or matte black finish.
- Motor-driven lifting design, with simultaneous drive for multiple movements. 4, Automatic power lift system with variable speed, Vertically Double silent sliding rail Operation & Digital synchronous positioning.
- Provides a protective function for HD screen monitors by cutting electricity off automatically if it reaches the monitor lift bottom and powering the screen on if it reaches the top
- Anti-pinching hand protection design for accidents during operation.
- The screen angle of the motorised monitor lift is adjustable, from 15 to 30 degrees as required; optional 120. Loop-in/Loop-out network. Cat6 video loopin/out optional.
- Lifting mechanism control via a switch button; 42 display control RS-232 port, content push to all screens, wireless RF remote, central control, and wireless network control.
- Optinal -Chairman/Secretary/ Delegate IDs, Automatic power on/off at lift position

Product name	Motorized retractable monitor lift
Model No.	SVAML-17.3T (T -Toughened Glass) , SVAML-17.3 (NON -Touch) ,
Material	Full aluminum alloy, Body thickness <70mm
Panel thickness	3mm panel
Screen Size	462mm*60mm*562mm (17.3 LED IPS screen) non touch
Screen Tilt Angle	Automatic 0-15 degree /Electric adjustable 0-30 degree
Color	Brushed aluminum silver / aluminum black matte
Connection Interface	1x HDMI, 4x USB (DATA,HDD, Mouse, Keyboard), RS232 I/O
Service Life	Above 20000 times
Working Sound	Less than 15 decibels
Format	16:09
Resolution	1920*1080
Viewing Angle	170(H)/160(V) - degree
Pixel resolution	0.2
Frequency	60Hz
Brightness	300 cd/m2
Contrast Ratio	1100:1
Response Time	16
Display Color	16.7 M (10 bit)
Power Consumption	<170W
Certification	CE,FCC,RoHS,(ISO9001:2015,14001:2015,45001:2018, 27001:2022 -IAF Certified)

SOLVISION TECHNOLOGY

27 Elder Road, Working
Surrey GU24 9HB UK
info@solvisionav.com

9 A, Blackwood Avenue,
Mentone, VIC- 3194
salesaustralia@solvisionav.com

629 Redstone Drive NE,
Calgary AB, T3N, 1KB Alberta
salescanada@solvisionav.com

SOLVISION INDIA

357-B, Udyog Vihar Phase 6, SECTOR
37, Pace City II Gurugram Haryana-
122001 -
salesindia@solvisionav.in