

Solvision TSV Series Wall Mount Speaker

TSV-G52, G62

High-end Wall Mounted Speaker

Water and dust protected IP55

- The Solvision Wall-Mount TSV Series universal surface speakers are compact, high-performance systems housed in rugged HIPS enclosures to ensure long-term durability and excellent sound quality. The speakers are IP55-rated, making them suitable for both indoor and outdoor applications. Designed for wide-range use, the TSV Series is ideal for commercial, educational, and public address installations.



Features

The TSV universal surface speakers are compact systems with rugged HIPS housing to ensure their durability and sound quality.

This series of speakers is rated to IP55. Designed for widespread use in outdoor applications which need good sound quality, like commercial pedestrian streets, pub streets, villas, swimming pools, golf courses, and playgrounds. It can also have extraordinary performance in indoor use: conference room, boardroom, and multi-functional room.

They are suitable for outdoor applications, and indoor applications are good as well.

This transformer with multi-tap selections for 100V/70V/8Ω input offers versatility and is suitable for professional audio and public address applications.

We offer black and white alternative colours or other spraying colours which are concerted to decoration, and it is fit for different environments.

Humanising design mounting bracket makes installation easy and fast, saving installation cost and time. You can also change the speaker's angle in order to control sound directivity.

Model No.	G52 B/W	G62 B/W
Rated Input	20W@100/70V ; 50W@8Ω	40W@100/70V ; 80W@8Ω
Max Input	50W@100/70V; 100W@8Ω	80W@100/70V; 160W@8Ω
High Impedance	83Ω, 167Ω, 333Ω, 667Ω, 1.33kΩ,	83Ω, 167Ω, 333Ω, 667Ω, 1.33kΩ,
Power Taps	100V: 20W, 10W, 5W, 2.5W; 70V: 10W, 5W, 2.5W, 1.25W	100V: 40W, 20W, 10W, 5W 70V: 40W, 20W, 10W, 5W
SPL (1W / 1m)	95dB	105dB
MAX SPL(Rated / 1m)	115dB@100/70V; 125dB@8Ω	125dB@100/70V; 130dB@8Ω
Frequency Response(-10dB)	50Hz~20kHz	50Hz~20kHz
Dispersion (4kHz / 1kHz)	80° (V) / 100°(H)	80° (V) / 100°(H)
Power Selecting Way	Rotating Selection Switch (100V/70V/8Ω)	Rotating Selection Switch (100V/70V/8Ω)
Material	Housing: HIPS (PP); Grille: Steel	Housing: HIPS (PP); Grille: Steel
Color	G52 B: Black; G52 W: White	G62 B: Black; G62 W: White
Temperature / Humidity	-30°C ~ 60°C; <95%	-30°C ~ 60°C; <95%
Water Protection	IEC529 IP55	IEC529 IP55
Speaker Component	5.25"Woofer + 1"Tweeter	6.25"Woofer + 1"Tweeter
Dimensions	255*186*180mm	L285*216*205mm
Weight	2.5kg	3.2kg
Mounting	U Type Mounting Bracket Or Optional Other Bracket	U Type Mounting Bracket Or Optional Other Bracket

SOLVISION TECHNOLOGY

27 Elder Road, Working
Surrey GU24 9HB UK
info@solvisionav.com

9 A, Blackwood Avenue,
Mentone, VIC- 3194
salesaustralia@solvisionav.com

629 Redstone Drive NE,
Calgary AB, T3N, 1KB Alberta
salescanada@solvisionav.com

SOLVISION INDIA

357-B, Udyog Vihar Phase 6, SECTOR
37, Pace City II Gurugram Haryana-
122001 -
salesindia@solvisionav.in