

Solvision FIT-W Series Wall Mount Speakers

SV-FIT-W5T/W5L/W8T/W8L

- SV-FIT W series are compact waterproof fashion speakers. The use of international advanced mold, thickened high-strength ABS cabinet, and cleverly designed mounting bracket can respond to any installation requirements. The dustproof and waterproof performance of the speaker is as high as IP66 grade. It is widely used in various all-weather environments in pursuit of sound quality.



Features

- All-weather speaker with a wide range of applications.
- Dustproof and waterproof grade conforms to IEC529 IP66 standard.
- Stunning and extraordinary sound quality.
- All-weather speaker designed for the professional audio and commercial audio markets.
- Excellent 5", 8" coaxial unit.
- The treble is transparent, bright, soft and not irritating.
- The bass is surging, powerful and thick.
- With 100V constant voltage or 8Ω version options.
- ABS enclosure and aluminum mesh, optional black and white.
- Specifically designed gravity cabinet to help improve directionality and versatile installation.
- The hidden mounting bracket provides quick and flexible installation.



SOLVISION TECHNOLOGY

27 Elder Road, Working
Surrey GU24 9HB UK
info@solvisionav.com

9 A, Blackwood Avenue,
Mentone, VIC- 3194
salesaustralia@solvisionav.com

629 Redstone Drive NE,
Calgary AB, T3N, 1KB Alberta
salescanada@solvisionav.com

SOLVISION INDIA

357-B, Udyog Vihar Phase 6, SECTOR
37, Pace City II Gurugram Haryana-
122001 -
salesindia@solvisionav.in

Solvision W Series Wall Mount Speakers

SV-FIT-W5T/W5L/W8T/W8L

Specifications

Model	SV-FIT W5T	SV-FIT W5L	SV-FIT W8T	SV-FIT W8L
Rated power	60W@100V	90W@8Ω	120W@100V	180W@8Ω
Max power	90W@100V;	135W@8Ω	180W@100V;	270W@8Ω
SPL(1W / 1m)	93dB SPL (125 Hz-12.5 kHz @1/3 octave frequency band)94dB SPL (250 Hz-4 kHz)		95 dB SPL (125 Hz-12.5 kHz @1/3 octave frequency band)96dB SPL (250 Hz-4 kHz)	
Max SPL (Rated / 1m)	112 dB SPL@110V	115 dB SPL@8Ω	118 dB SPL@110V	120dB SPL@8Ω
Frequency response (-10dB)	80Hz~20kHz		70Hz~20kHz	
Diffusion Angle (4kHz / 1kHz)	115 ° cone (+46°/-46 °, 500Hz to 6kH)			
Power selection method	Phoenix terminal interface			
Material	Enclosure: ABS; Mesh cover: metal			
Color	Black; White			
Operating temperature/humidity	-30°C ~ 60°C; <95%			
Dustproof and waterproof grade	IEC529 IP66			
Speaker unit	5.25" coaxial unit		8" coaxial unit	
Dimensions	160 (W) x 328(H) x 192(D)		230 (W) x 470(H) x 257(D)	
Weight (1 pc)	5.7kg	6kg	8.5kg	9kg
Installation	Hidden mounting bracket			
Gross weight	13.4kg, 2 pcs	14kg, 2 pcs	19 kg, 2 pcs	20 kg, 2 pcs
Safety	CE,FCC,RoHS,(ISO9001:2015,14001:2015,45001:2018, 27001:2022 -IAF Certified)			

SOLVISION TECHNOLOGY

SOLVISION INDIA